



4 display orientation, 7 display modes



## Feature

- New contracted design, has contemporary feeling extremely
- Display content increase perfusion index
- Low power consumption; battery-low indicator
- Adjustable brightness signal inadequacy prompt
- Can remember the brightness settings and display mode
- Automatically power off
- CE mark and FDA approved

## Model No: **MD300CN360**

### Specifications

Application range	Adult and pediatrics	Measurement range	SpO <sub>2</sub> : 70~100% PI: 0.3~20% Pulse rate: 30~250bpm
Resolution	SpO <sub>2</sub> : 1% Pulse rate: 1bpm PI: 0.1%	Measurement parameters	SpO <sub>2</sub> , PR, PI, Pulse bar, waveform
Dimension	60mm(L)* 32mm(W)* 30mm(H)	Weight	55±5g (including batteries)
Display type	OLED and LED display	Accessories	1pc lanyard, 2pcs AAA-size batteries, 1pc instruction manual
Accuracy	SpO <sub>2</sub> : 70~100%, ±2%; 0~69%, no definition; Pulse rate: 30~99bpm, ±2bpm; 100~250bpm, ±2% PI: 0.2~1.0%, ±0.2 digits; 1.1~20%, ±20%;		
Power requirements	Two AAA 1.5V, 600mAh alkaline batteries could be continuously operated as long as 24 hours		